

Extech Infrared Thermometers

Mini IR Thermometers

Compact thermometers with choice of 500°F or 1200°F maximum reading

- Model 42500 measures -4 to 500°F (-20 to 260°C) with 1° resolution
- Model 42510A measures -25 to 1200°F (-50 to 650°C) with 0.1° resolution up to 1000°
- Built-in laser pointer and backlit LCD display
- Adjustable emissivity (42510A)
- Field of view: 42500 6:1, 42510A 12:1
- Complete with 9V battery and carrying case



▲ **Model 42510A**

Dual Laser IR Thermometers

Two laser pointers converge to 1" target spot

- Measure to 1800°F (1000°C) with 1° resolution
- 12" or 30" laser convergence distance
- Fast 0.15 second response time
- White backlit dual LCD display
- Adjustable emissivity increases accuracy
- Lock function for continuous readings
- Adjustable high/low setpoints with audible alarm alerts
- Complete with 9V battery and carrying case



▲ **Model 42512**

High Temperature IR Thermometer

Measures surface temperature to 1832°F with 50:1 distance to target ratio

- Measures small surface areas at greater distances
- Adjustable emissivity increases accuracy for different surfaces
- Displays MAX, MIN, average and difference (MAX-MIN) values
- Audible high/low alarm alerts user when temperature exceeds set limits
- Large, backlit LCD display with automatic Data Hold feature
- Complete with 9V battery and hard carrying case



▲ **Model 42545**

IR Thermometer with Wireless PC Interface

Wireless USB interface transmits temperature data to a PC

- Wide range (-58 to 1922°F / -50 to 1050°C)
- High 30:1 distance to target ratio
- Manual or Automatic emissivity
- Type K probe for accurate measurements on different surfaces
- Transmit continuous readings to the remote receiver with PC connection via USB CABLE
- Complete with transmitter base, receiver with USB cable, type K probe, PC software, 9V battery, AC adapter & case



▲ **Model 42560**

ORDERING INFORMATION

EX/42500	500° Mini IR Thermometer
EX/42510A	1200° Mini IR Thermometer
EX/42511	Dual Laser IR Thermometer - 12" Convergence
EX/42512	Dual Laser IR Thermometer - 30" Convergence
EX/42545	High Temperature IR Thermometer
EX/42560	IR Thermometer with Wireless PC Interface
EX/IR201	Pocket IR Thermometer

Pocket IR Thermometer

Handy troubleshooting thermometer with Laser pointer

- Measures from -58°F to 518°F (-50° to 270°C)
- Built-in laser pointer to improve aim
- Fixed emissivity (0.95) covers 90% of surface applications
- 6:1 field of view
- Complete with two AAA batteries and carrying case



▲ **Model IR201**

SPECIFICATIONS

Model	42500	42510A	42511	42512	42545	42560	IR201
Temperature: (non-contact)	-4 to 500°F -20 to 260°C	-25 to 1200°F -50 to 650°C	-58 to 1100°F -50 to 600°C	-58 to 1832°F -50 to 1000°C	-58 to 1832°F -50 to 1000°C	-58 to 1922°F -50 to 1050°C	-58 to 518°F -50 to 270°C
Temperature (Type K):	---	---	---	---	---	-58 to 2498°F -50 to 1370°C	---
Basic Accuracy: (non-contact)	±2.5% of reading or ±4°F / 2°C (whichever is greater)	±1% of reading ±2°F / 1°C	±1% of reading ±2°F / 1°C	±1% of reading ±2°F / 1°C	±2% of reading ±4°F / 2°C <932°F (500°C)	±2% of reading or ±4°F / 2°C (whichever is greater)	±2.5% of rdg ±3°F / 2°C
Max. Resolution:	1°	0.1° up to 999.9°	0.1°	0.1°	0.1° up to 199.9°	0.1°	1°
Emissivity	0.95 fixed	0.1-1.00 adjust	0.1-1.00 adjust	0.1-1.00 adjust	0.1-1.00 adjust	0.1-1.00 adjust	0.95 fixed
Field of View: (Distance to Target)	6:1	12:1	12:1	30:1	50:1	30:1	6:1
Dimensions:	3.2 x 1.7 x 6.7" 82x44x170mm	3.2 x 1.6 x 6.3" 82x42x160mm	5.7 x 4.1 x 1.6" 146x104x43mm	5.7 x 4.1 x 1.6" 146x104x43mm	3.9 x 2.2 x 9" 100x56x230mm	3.9 x 2.2 x 9" 100x56x230mm	3.7 x 2 x 1" 94x51x25mm
Weight	4.9oz (140g)	6.4oz (180g)	5.7oz (163g)	5.7oz (163g)	10.2oz (290g)	10.2oz (290g)	2.7oz (76g)
Warranty:	3 years	3 years	3 years	3 years	3 years	3 years	1 year