

Yokogawa Insulation Testers

2406E Analog Insulation Tester

- 3 Ranges
- Discharge Function
- Portable Case for Hanging Tester from Neck
- Sky-Blue EL Illumination



2406E ▶



MY10 Analog Insulation Tester

- Single Range Models
- AC Voltage Measurement Function (needle and LED)
- Automatic Discharge Function (LED)
- Easy to Use Pull-Up Switch



MY10 ▲



MY40 Digital Insulation Tester

- Four Voltage Ranges
- Memory Function
- Comparator Function with Sound Alert
- Auto Discharge Function
- Large LCD Display with Stable Indication
- AC Voltage/Resistance Measuring Functions
- Conductor Resistance Measurement



MY40 ▲



Model	Rating	Measure	Display	Illumination	
YE/2406	31	50V / 10M 125V / 20M	300V AC	Analog Meter	Back-lit EL display (41/42/43/44/45)
	41				
	42				
	32	125V / 20M 250V / 50M			
	43				
	44				
	33	125V / 20M 250V / 50M 500V / 100M			
	43				
	44				
YE/MY10	01	125V / 20M	250VAC	Analog Meter	Phosphorescent scale
	02	250V / 50M	300VAC		
	03	500V / 100M	500VAC		
	04	500V / 1000M			
	05	1000V / 2000M			
YE/MY40	01	125V / 200M 250V / 200M 500V / 2000M 1000V / 2000M	600VAC	3.5 digit & 400Ω	LED Lighting bargraph LCD

Lifetime Warranty on All Models

Dimensions:

2406	4.7"x4.3"x2.4" (120x110x60mm)
MY10, MY40	4.9"x4.1"x2.1" (125x103x53mm)

Power:

2406	6 AA Batteries (included)
MY10, MY40	4 AA Batteries (included)

Fluke Infrared Thermometers

- Single dot laser sighting
- Pistol Grip housing
- 1% / 1°C accuracy
- Dual backlit display
- Reading hold
- Protective rubber boot



Fluke 62

Fluke 68

ORDERING INFORMATION

Fluke 62	Mini Infrared Thermometer w/ holster
Fluke 63	Infrared Thermometer w/ holster & case
Fluke 66	Infrared Thermometer w/ holster & case
Fluke 68	Infrared Thermometer w/ holster & case
Fluke 68IS	Intrinsically safe Infrared Thermometer w/ case
FL/H6	Holster

SPECIFICATIONS

MODEL	62	63	66	68
Range °C	-30 to 500	-32 to 535	-32 to 600	-25 to 760
Range °F	-20 to 932	-25 to 999	-25 to 1100	-25 to 1400
Spot Distance	10:1	12:1	30:1	50:1
Emissivity	0.95	0.95	0.10-1.00	0.10-1.00
Min/Max/Avg	Max	Max	All	All
Datalogging	--	--	12 point	12 point
Hi/Lo Alarms	--	Yes	Yes	Yes
RTD probe*	--	--	Yes	Yes
Warranty	2 yr	1 yr	1yr	1yr

Response Time: <500 mS

Battery: 9V alkaline (included)

Size: 62: 6x4x1.5" (152x101x38mm)
63, 66, 68: 8x6x2" (200x160x55mm)

Operating Temp: 0 to 50°C, <90% RH non-condensing

*contact temperature measurement with option RTD probe