

## ENM Hour Meters & Counters

### Electronic LCD Hour Meter/Counter

- 6 digit LCD Display
- Non-volatile Memory
- Up/down Counting
- Resettable
- Shock Resistant

#### SPECIFICATIONS

Display:	99999.9 (hour meter)
	0 to 999999 (up counter)
	999999 to 0 (down counter)
Digit Height:	5mm
Power:	8-28VDC
Count Speed:	100/second max.
Terminals:	3/16" male quick connects
Temperature:	-40 to 85°C

#### ORDERING INFO

Example T1121AB

<b>A</b>	<b>Type</b>	
	T	Timer
	C	Up Counter
	D	Down Counter
<b>B</b>	<b>Style</b>	
	1121A	Screw Mount
	1131A	Clip Mount
	1141A	Rectangular Clip Mount
<b>C</b>	<b>Finish</b>	
	B	Black
	S	Stainless

T1121A ▶



T1131A ▲



T1141A ▶

### Hour Meter & Battery Discharge Gauge

- 6 Digit LCD Hour Display
- 10 Segment LED Battery Charge Indicator
- Fits 2" Diameter Hole
- -10 to 65°C Temperature Range

#### ORDERING INFO

Model	Voltage
PT271AB1	12/24VDC
PT272AB1	24/36VDC
PT273AB1	36/48VDC
PT274AB	70/80VDC




PT271AB1 ▲

T51D ▶



T41E ▶



### Electromechanical Hour Meters

- Low Power Consumption
- Solid State Drive Circuit
- Mechanical Indicator Retains Reading
- Quartz Crystal Timing
- Quiet Operation
- Sealed, Tamperproof Plastic Case

#### SPECIFICATIONS

Display:	99999.9 hours, auto recycle to zero
Digit Height:	0.125"
Temperature:	-30 to 65°C
Terminals:	1/4" male quick connects

#### ORDERING INFO

Example T51D4

<b>A</b>	<b>Type</b>	
	T41	DC powered hour meter
	T51	AC powered hour meter
<b>B</b>	<b>Style</b>	
	D	Front panel mount (clips)
	E	Back of panel mount (screw holes)
	F	48x48mm panel mount (clips)
<b>C</b>	<b>Power</b>	
	1	230VAC 50/60Hz
	2	115VAC 50/60Hz
	4	24VAC 50/60Hz
	45	10-80VDC

T41F ▲

