

Weschler AC Elapsed Time Meters (formerly Yokogawa)

Type 240

- Meets ANSI C-39.1
- Five Case Styles
- Wide Selection of Ranges
- Weather Resistance
- UL Recognized

SPECIFICATIONS

Accuracy	Matches frequency control of power system
Vibration Shock	Meets ANSI Specification C39.1
Materials	Case of clear LEXAN®, frame of Noryl®, brass terminal studs, Lucite® front covers
Presentation	6-digit counter in hours and tenths of hours or minutes and tenths of minutes
Insulation Level	Operating at 120, 208, 240 or 480 volts AC, will pass Hi-pot of 2000 VRMS for one minute
Motor	3 Watts typical

ORDERING INFORMATION

1 Insert:	1 - for Register in Hours and Nonresetable
	2 - for Register in Hours and Resetable
	3 - for Register in Minutes and Nonresetable
	4 - for Register in Minutes and Resetable

AC Elapsed Time Meters-Type 240 Big Look

Voltage/Freq.	2½" Size	3½" Size
120V-60 Hz	24021 1 AAAB	24031 1 AAAB
120V-50 Hz	24021 1 ADAB	24031 1 ADAB
208/240V-60 Hz	24021 1 ABAB	24031 1 ABAB
208/240V-50 Hz	24021 1 AEAB	24031 1 AEAB
480V-60 Hz	24021 1 ACAB	24031 1 ACAB

AC Elapsed Time Meters-Type 240 Square Case

120V-60 Hz	24061 1 AAAD	24071 1 AAAD
120V-50 Hz	24061 1 ADAD	24071 1 ADAD
208/240V-60 Hz	24061 1 ABAD	24071 1 ABAD
208/240V-50 Hz	24061 1 AEAD	24071 1 AEAD
480V-60 Hz	24061 1 ACAD	24071 1 ACAD

AC Elapsed Time Meters-Type 240 Round Case

120V-60 Hz	24063 1 AAAE	24073 1 AAAE
120V-50 Hz	24063 1 ADAE	24073 1 ADAE
208/240V-60 Hz	24063 1 ABAE	24073 1 ABAE
208/240V-50 Hz	24063 1 AEAE	24073 1 AEAE
480V-60 Hz	24063 1 ACAE	24073 1 ACAE

AC Elapsed Time Meters-Type 240 Back of Panel (One Size Only)

Voltage/Freq.	Catalog No.
120V-60 Hz	24000 1 AAAA
120V-50 Hz	24000 1 ADAA
208/240V-60 Hz	24000 1 ABAA
208/240V-50 Hz	24000 1 AEAA
480V-60 Hz	24000 1 ACAA



Round Case ▲



New Big Look Panel Mounted ▲



Square Case ▲



Back of Panel Unmounted ▲