

Weschler Indoor Enclosures

- NEMA 4X & UL508-4X Indoor Rated
- ABS/Polycarbonate Blend
- Non-Metallic Hinge & Latch
- UL94-5VB Flammability
- Includes Stainless Wall Mounting Bracket



ORDERING INFORMATION

Model	Width	Height	Depth
NBB-10240	5.90	5.90	3.57
NBB-10241	6.79	10.75	4.33
NBB-10243	7.47	11.28	5.50
NBB-10251	10.65	14.55	5.92
NBB-10247	11.73	15.68	6.30
NBB-10245	13.00	13.00	7.04

Dimensions in inches. For inside dimensions, subtract 0.9" from Width & Height, 0.3" from Depth

Pyromation Thermowells

Stepped construction increases speed of response while maintaining mechanical strength

- 0.260" bore standard
- 304 or 316 stainless steel



ORDERING INFORMATION

Insert Code for Each Letter to Select Catalog Number.

Example S4C608

S4

A Female fitting

C	1/2" NPT
D	3/4" NPT
E	1" NPT

B Overall Length

4	4"
6	6"
9	9"
12	12"

C Material

08	316 SS
09	304 SS

Other lengths, diameters, threads & materials available on request.

Adalet Explosionproof Meter Housings

NEW

- Copper-free Aluminum Casting
- Window Cover
- Suitable for Meters, Instruments & Control Equipment



XJO



XJM



Model	Outside* (W H D)			Window	Opening	Inside (W H D)			Under glass
Certifications: UL1203 & CSA C22.2 No. 25 & 30 - Class I, Group B, C, D & Class II Groups E, F, G; UL50 Type 4									
XJMAGCHN4	7 3/4	7 3/4	8 1/2	5 1/4 dia	5 3/8 dia	6 3/4	6 3/4	5	6 7/8
XJMGCHN4	7 3/4	7 3/4	11 1/2	5 1/4 dia	5 3/8 dia	6 3/4	6 3/4	8	9 7/8
XJKGCHN4	10 3/4	12 3/4	8 15/16	6 11/16 dia	9 dia	9 1/2	11 1/2	6 1/8	6 7/8
XJKAGCHN4	10 3/4	12 3/4	10 15/16	6 11/16 dia	9 dia	9 1/2	11 1/2	8 1/2	8 7/8
XJNGCHN4	13 1/8	14 3/8	9 13/16	8 dia	10 3/4 dia	11 1/2	12 3/4	6	6 5/8
Certifications: UL1203 & CSA C22.2 No. 25 & 30 - Class I, Group C, D & Class II Groups E, F, G; UL50 Type 4									
XJOGCN4	9	9	7 9/16	5 1/4 dia	7 x 7	8	8	5	5 13/16
XJSWGCN4	6 1/8	6 1/8	5 5/8	**	5 x 5	5 1/4	5 1/4	4 1/2	6 1/8

Dimensions in inches *excluding mtg tabs **suitable for 3 1/2" rectangular & 4 1/2" round meters

Misc.