

Simpson Analog VOM

- Industry Standard Model 260
- 36 Measurement Ranges
- Mirrored Scale
- CAT III-600V (260-95)
- 10A AC (260-95)
- 1000V AC/DC Max (260-8)

ORDERING INFORMATION

(Test Leads Included)			ACCESSORIES		
Cat. #	Model #	Description	Cat. #	for Model	Description
SI/12388	260-8	General Purpose, Phenolic Case	SI/00043	260-8, 8P	Probe Set, threaded w/clips
SI/12391	260-8P	Relay Protected	SI/00125	260-8XI, 8XPI	Probe Leads w/Screw-On Alligator Clips
SI/12389	260-8RT	Roll Top Case	SI/00834	Any 260-8	Black nylon padded case
SI/12392	260-8PRT	Relay-Protected, w/Roll Top Case	SI/00805	Any 260-8	Black Leatherette case
SI/12395	260-8XI	Yellow ABS Plastic Case	SI/00541	260-8XI, 260-8XPI, 9S, 9SP	250A AC Clamp
SI/12396	260-8XPI	Yellow Case, Relay-Protected	SI/00545	260-8, 8P, 8RT, 8PRT, 95, 95P	250A AC Clamp
SI/12397	260-9S	Safety VOM Orange, with Case	SI/00425	260-8X, 9	Screw-on alligator Clips
SI/12398	260-9SP	Safety VOM Protected, with Case			



▲ 260-8

▼ 260-9S



Triplett Analog VOM

- 58 Ranges & Functions (Model 60-NA)
- Withstands 5 Foot Drop
- 3 Year Warranty
- Mirrored Scale

60 ▶



ORDERING INFORMATION

TR/3145	Model 60 VOM (Orange Case)	Test Leads
TR/3151	Model 60-NA (Gray Case)	TR/79-373 Miniature Clip Leads (female jack)
Carrying Cases		TR/79-374 48" Test Leads w/ Screw-On Alligator Clips (female jack)
TR/10-823	639 Carrying Case (Top Opening)	AC Amps Clamp-On
TR/10-2739	639-A Carrying Case (Snap back Cover)	TR/3264 Model 101-G Line Separator
TR/4152	639-C Padded Cordura Carrying Case	TR/60-211 Model 10 Clamp-On AC AMP Adaptor (60, 60-NA)
		TR/79-417 6' Attachment Leads (60/ 60-NA to Model 10)

Triplett Battery Tester

Multi-Battery Tester for Sealed Lead-Acid, NiMH, NiCad and Li-Ion Batteries

- Load Tests 5.75 Volt to 19.99 Volt Batteries
- Works on Batteries from 1 to 20 Amp-Hours
- Polarity Reversal Indication and Protection
- Powered by Battery Being Tested
- Large, Bright LED Display
- Selectable DC Amps Polarity

3276 ▶



Test batteries in security systems, UPS's, emergency lighting, power tools, lawn equipment, toys.

SPECIFICATIONS

Operating Voltage:	5.75 to 19.99 volts DC
Resolution:	0.01 volts
Accuracy:	+/- 0.03 volts
Load Current:	Typically 600mA at 6 volts, 1.2 Amps at 12 volts
Measurement Time:	10 seconds max.
Display:	3-1/2 digit
Dimensions:	6 x 3.25 x 1.25 in

ORDERING INFORMATION

TR/3276	Chek-A-Cell Battery Tester
---------	----------------------------