

ENVIRONMENTAL TESTERS

AIR QUALITY DATA LOGGER

MODEL 1510

Monitor CO₂, temperature, and humidity for a healthy environment



FEATURES

- CO₂, temperature, and humidity logger
- Free app available from Android and Google Play stores
- Compact and stand-alone: for mounting or portable use
- User-friendly: comfort indicators based on the CO₂, temperature and humidity levels
- Accurate: complies with the latest standards concerning air quality monitoring
- Quick, simple data download using supplied DataView® software
- On-site calibration test module with adapter, tube and software for adjusting the zero and thresholds

PRODUCTS INCLUDE

- Meter in carrying pouch
- Adapter - US wall to USB
- 6ft USB cable
- 2 AA batteries
- Quick start guide
- User manual and DataView® application software included on USB Drive

CATALOG NO.	DESCRIPTION
2138.08	Air Quality Logger Model 1510 (Gray)
2138.09	Air Quality Logger Model 1510 (White)
Accessories/Replacement - available on website store from www.aemc.com	
2138.61	Wall Mount Holster (Gray)
2138.62	Desktop Stand (White)
2153.78	Adapter - US Wall Plug to USB
2138.67	Wall Mount Holster (White)

SPECIFICATIONS

CO ₂ Measurement	
Measuring Principle	Non-dispersive infrared (NDIR) technology
Type of Sensor	Double-beam infrared cell sensor
Measurement Range	0 to 5000 ppm
Accuracy (CO ₂)	±50 ppm ±3% of value measured
Response Time, 63%	< 200 seconds
Resolution	1 ppm
Temperature Measurement	
Type of Sensor	CMOS
Units	°C or °F
Measurement Range	14° to 140°F (-10° to 60°C)
Accuracy	±1.0°F (±0.5°C)
Resolution	0.1°F (0.1°C)
Humidity Measurement	
Type of Sensor	Capacitive
Measurement Range	5 to 95% RH
Accuracy	±2% RH
Resolution	0.1% RH
General	
Recording Interval	Programmable from 1 minute to 2 hours
Storage	> 1 million measurements
Alarm	Yes
Backlighting Display, Hold, Min & Max	Yes
Auto Power OFF	Yes (in portable mode only)
Dimensions/Weight	4.92 x 2.58 x 1.26" (125 x 65.5 x 32mm)/ 6.7oz (190g) with batteries
Protection	IP40
Compliance	IEC 61010-1, 50V CAT II - IEC 61326-1
Power Supply	Alkaline batteries: 2 AA or rechargeable battery connection to 120V 60Hz line/USB to wall adapter
Communication	Bluetooth (Class I) wireless communication/USB link; the product is then recognized as a USB drive for easy file transfer
Mounting	Optional padlockable wall mount (padlock is not included), optional desktop stand and tear drop wall hook
DataView® Software	Graphic representation or as table of values, data export, real-time mode calculation of the confinement index with selection of presence periods & report generation