

DPM1000 Power clamp



- AC/DC Voltage to 1000V
- AC/DC Current to 1000A
- True RMS
- Resistance 100k Ω
- LCD Display
- Phase rotation indication
- Inrush peak current
- Auto backlight display
- Frequency measurement
- Capacitance measurement
- Power Factor Measurement
- Watt measurement to 1MW
- Harmonic measurement
- Harmonic distortion
- Diode test
- Non-contact volt alert
- Continuity Beeper
- Data Hold/Min-Max/Peak Hold
- Bright LED torch
- Temperature to 1000° C
- Carrying holster/pouch
- CAT IV 600V Rating
- Bluetooth/Megger Link™ APP
- Supplied with carry case

DESCRIPTION

The new Megger DPM1000 Power Clamp meter combines the functionality of power meter, harmonics meter and data logger in one easy to use package. The design meets the requirements of BSEN 61010-1 CAT IV 600V for supply side applications. A large backlit LCD clearly displays all measurements that turns on at the touch of a button or when rotating the selection dial. It also automatically switches off to save battery consumption.

The DPM1000 can measure DC, AC, pulsed and mixed currents up to 1000 A simply by clamping the jaws around the appropriate conductor, whilst voltages up to 1000 V AC or DC may be measured by the supplied test leads, Where power measurements are to be made both techniques above are performed simultaneously. All power related parameters including energy consumption, frequency, total harmonic distortion, distortion factor and capacitance. It features auto-ranging and has 3 phase rotation indication.

The DPM1000 measures Single and 3 phase active power and power factor, the harmonic content of the signal, up to the 25th harmonic can be displayed. Temperature measurements can be made up 1000°C using the thermocouple provided.

The DCM1000 is ideally suited to measuring mains power quality and applications in the development, installation, maintenance and repair of equipment and devices used in power electronics and power engineering. The unit has an internal torch that lights during the operation of the clamp and automatic non-contact voltage detection for identification of live circuits.

The DPM 1000 may be used to perform data logging to its internal non-volatile memory. You can record a maximum of 9999 readings/records to the memory over a period of time and download the data to produce graphs and reports. The record rate can be set from 1 sec to 600 sec. The accuracy of the timer is within 3 seconds per hour.

The meter uses low-power Bluetooth v4.0 wireless technology to transfer real-time data to the free Megger Link™ app, available for both iOS and Android. The maximum communication range in open air is approximately 10 m. This function is invalid for Inrush and Phase Rotation.

The DPM1000 is supplied complete with test leads and Thermocouple Probe in full sized Carry case.

DPM1000 Power clamp

SPECIFICATIONS

ACA Range	100A – 1000A
• Resolution	0.01A
• Basic Accuracy	± (1.5% +5d) at 50-500Hz
• Conversion Type	AC+DC True-RMS
ACV Range	100V~1000V
• Resolution	0.01V
• Basic Accuracy	± (1.5%+5d) at 50Hz~500Hz
• Input Impedance	3.5MΩ
• Overload Protection:	1000V rms
DCA Range	100A – 1000A
• Resolution	0.01A
• Basic Accuracy	± (1.5% +5d)
DCV Range	100V~1000V
• Resolution	0.01V
• Basic Accuracy	± (0.7%+2d)
• Input Impedance	3.5MΩ
• Overload Protection:	1000V rms
AC+DCV Range:	100V~1000V
• Resolution	0.01V
• Basic Accuracy	± (1.7%+7d)
• Input Impedance	3.5MΩ
• Overload Protection:	1000V rms
Watt:	10KW~1MW
• Resolution	1W
Power Factor:	-1.00 ~ 1.00
• Resolution	0.01
• Basic Accuracy	± 5d
T.H.D:	0.1% ~100%
• Resolution	0.1%
• Basic Accuracy	± (3.0%+10d)
Harmonics:	0.1% ~100%
• Resolution	0.1%
• Basic Accuracy	± (5.0%+10d) For order 1-12 ± (10.0%+10d) For order 13-25
Resistance	1kΩ – 100kΩ
• Resolution	0.01Ω
• Basic Accuracy	± (1.0% + 5dgt)
• Overload Protection:	1000V rms

Continuity Beeper: <30Ω, 2.KHz tone buzzer

Diode Test:

- Open Circuit Voltage ± 1.8 V max

Capacitance 4μF – 4000μF

- Resolution 1nF
- Basic Accuracy ± (1.9%+8d)
- Overload Protection: 1000V rms

Frequency Counter 20.00Hz ~ 10.00KHz

- Resolution 0.01Hz
- Accuracy ± 0.5%+3d

Temperature -58°F ~1832°F

- Resolution 32.2°F
- Accuracy ± (1.0%+37.4°F)
- Overload Protection: 1000V rms

Sampling Rate 3times/sec

Overload Indication "OL" or "-OL"

Low Battery Indication

Auto Power Off 15 Minutes

Operating Temperature 32°F~122°F, ≤80% RH

Storage Temperature 14°F ~ 122°C

Temperature Coefficient 0.2 x (Spec. Acc)/°C,
<64.4°C or>82.4°C

International Standard IEC/EN 61243-3:2014

Safety Standard: IEC 61010-1, Designed to meet
UL61010 Spec CAT IV 600V,
CAT III 1000V

Maximum Conductor Size 40mm

Maximum Busbar Size 61 x 12mm

Power Requirement AAA Size Battery 1.5V x 6

Battery Life in hours: 50

Size 103mm(W) x 258mm (L)
x 55mm(H)

Weight: (with battery) 600g

Specification subject to change without notice

Authorized Distributor:

WESCHLER INSTRUMENTS

phone: 800-903-9870 440-378-6580

fax: 800-903-9590 440-238-0660

www.weschler.com info@weschler.com

ORDERING INFORMATION

Description	Part number
-------------	-------------

DPM1000 power clamp meter	1013-356
----------------------------------	-----------------

Included accessories

DCM 4mm Spare Lead Set	1013-358
------------------------	----------

TP-90 Thermocouple Probe	1013-364
--------------------------	----------

Hard Carry Case	
-----------------	--